

OPERMART data sheet

Product
code:20240192Condition:UsedPositive
feedback:0 % Positive
feedback:

Brand: ATB Category: Wounded Rotor induction Return policy: NO

Total: 0 Seller ID: farha4OSZW Guarantee: NO

Price: Seller store: Fire Zone: $\frac{\text{IEC EX d IIIA}}{\text{T6 Dc}}$

Short description: 3-phase induction (asynchronous) motors 2-pole / 4-pole



General data	Electrical data	Mechanical data	
Lifting Lugs	Temperature class	Temperature winding protection	
Feedback Device	Max torque	AIR FLOW DIRECTION	
Serial number	Electrical time constant	AIR FILTER	
Frame size	Service factor	Brushed -Motor Type	
Cooling type	Space heater	Long life brush system	
Rotor weight	Rated Voltage - 6.3 kV	Terminal box position	
Year made	Rotor current 567 mA	Direction of rotation	
Factory location	Rated power 950 kW	Duty cycle(Type of duty)	
Body Material	Number of Phase	Number of speed	
Mounting	Rated frequency 60 Hz	Temperature rise	
life time	Rated Speed - 1790 rpm	No load Noise (SPL 1 meter)	
Electrical data	Rated Current	BRAKE	
Torque Constant	- Input power	DE bearing	
Rated slip	- Power factor	NDE bearing	
Winding Type	- Rated torque	Shaft type	
Phase winding inductance	- Locked rotor torque	shaft diameter	
Phase winding resistance	- Breakdown torque	shaft length	
Dielectric Strength	- Connection type	Paint color	
Rotor inertia	- Starting method	Temperature Bearing protection	
Detent torque	- Insulation class	Mechanical Bearing protection	
Locked Rotor Time (Cold)	- Efficiency class	Position of main cable entry	
Locked Rotor Time (Hot)	- Efficiency (%)	Cable gland size	
Rotor voltage 789	9 V Number of poles	Bearing type	
Ground Lug	Mechanical data	Environmental data	
Base RPM	Fan blade	Altitude ? ASL	
Hot start number	Air flow	Design Humidity	
Cold start number	Impeller	Enclosure Protection	