

Product code:	20240149	Condition:	Refurbished By Factory	Positive feedback:	0 % Positive feedback
Brand:	ATB	Category:	Squirrel cage induction	Return policy:	NO
Total:	1	Seller ID:	farha4OSZW	Guarantee:	NO
Price:		Seller store:		Fire Zone:	ATEX *** G EX n I B T5 Db *



Short description: 3-phase induction (asynchronous) motors 2-pole / 4-pole 3-phase induction (asynchronous) motors 2-pole / 4-pole 3-phase induction (asynchronous) motors 2-pole / 4-pole 3-phase induction (asynchronous) motors 2-pole / 4-pole 3-phase induction (asynchronous) motors 2-pole / 4-pole 3-phase induction (a

General data	Electrical data	Mechanical data
Serial number Gt6565Hfr878	Ground Lug -	Cable gland size 95
Frame size T664	Hot start number -	Shaft type sleeve
Cooling type IC 34	Cold start number -	Position of main cable entry top
Rotor weight 450 Kg	Starting method -	Mechanical Bearing protection Yes
Year made 2009	Insulation class -	Temperature Bearing protection No
Factory location Italy	Rated Voltage 433 V	Temperature winding protection No
Body Material -	Number of poles -0.0004	Paint color gray
Mounting B3	Rated frequency 50 Hz	shaft length 223 mm
Lifting Lugs Yes	Rated Speed 1490 rpm	shaft diameter 234 mm
Electrical data	Rated Current -	NDE bearing 134qwrq
Efficiency class -	Power factor -	DE bearing e2132
Rated power -0.0007 kW	Number of Phase -	BRAKE No
Efficiency (%) -	Rated torque -	No load Noise (SPL 1 meter) 12 dB
Service factor -	Locked rotor torque -	Environmental data
Space heater -	Breakdown torque -	Altitude ? ASL 1000 m
Rated slip -	Connection type -	Design Humidity 45
Locked Rotor Time (Hot) -	Mechanical data	Enclosure Protection IP66
Locked Rotor Time (Cold) -	Number of speed 1 rpm	Operating Temperature 54 C
Rotor inertia -	Direction of rotation CCW	Humidity Range (%) 87
Winding Type -	Bearing type Roll	Ambient Temperature Range 56 C