

Product code:	20240116	Condition:	Pre Owned	Positive feedback:	0 % Positive feedback
Brand:	ABB	Category:	Squirrel cage induction	Return policy:	NO
Total:	30	Seller ID:	sshamzRCQ6	Guarantee:	NO
Price:		Seller store:		Fire Zone:	ATEX * II 3 G EX p II B T5 Db *

Short description: Abb electromotr in good conditions



General data	Electrical data	Mechanical data
Serial number	Ground Lug	Cable gland size
82756887656	-	-
Frame size	Hot start number	Shaft type
T700	4	-
Cooling type	Cold start number	Position of main cable entry
IC6	5	-
Rotor weight	Starting method	Mechanical Bearing protection
9500 Kg	DOL	-
Year made	Insulation class	Temperature Bearing protection
2011	F	-
Factory location	Rated Voltage	Temperature winding protection
Germany	011 kV	-
BODY MATERIAL	Number of poles	Paint color
Cast Iron	3	-
Mounting	Rated frequency	shaft length
B3	50	555 mm
Lifting Lugs	Rated Speed	shaft diameter
YES	375	76 mm
Electrical data	Rated Current	NDE bearing
Efficiency class	990 A	57567568
95	Power factor	DE bearing
Rated power	.91	423235
8 MW	Number of Phase	BRAKE
Efficiency (%)	3.01	No
95 %	Rated torque	No load Noise (SPL 1 meter)
Service factor	5555 N.m	324 dB
1	Locked rotor torque	Environmental data
Space heater	6000 N.m	Altitude ? ASL
Yes	Breakdown torque	1000 m
Rated slip	6500 N.m	Design Humidity
3	Connection type	-
Locked Rotor Time (Hot)	-	Enclosure Protection
7 Sec	Mechanical data	IP76
Locked Rotor Time (Cold)	Number of speed	Operating Temperature
8 Sec	-	60 C
Rotor inertia	Direction of rotation	Humidity Range (%)
5345 g.cm?	CCW	95
Winding Type	Bearing type	Ambient Temperature Range
-	-	50 C